



No Limits

HUMMEL products are available from MARYLAND METRICS
P.O.Box 261 Owings Mills, MD 21117 USA
phones: (410)358-3130 (800)638-1830 faxes: (410)358-3142 (800)872-9329
email: sales@mdmetric.com web: <http://mdmetric.com>

IP 67 – liquid tight when disconnected



Using a rubber diaphragm makes this connector liquid tight either connected or disconnected (NEMA 4 = IP 67).

Bulkhead Connector



Bulkhead connectors accept plugs on both sides. They are rugged, liquid tight and available in all number of poles.

Simple EMI / RFI shielding



An integrated metalized EMI clamping insert grounds to the the braid significantly simplifying the assembly of the elbow connector.

MULTI Seal Connector



A large selection of standard MULTI seal inserts allow strain relief of several individual conductors on one single connector.

Flexible Cable Protection



In addition to the integrated strain relief, the flex nut adds kink protection to a cable - available for all connector sizes.

Adaptor flange



To secure loose connections, an adaptor flange can be attached to a straight connector.

12-point hex and knurled nut



This special nut makes connection simple by either tightening the connector manually (knurled nut) or with a wrench (12-point hex).

Conduit Attachment



Flexible corrugated conduit can be attached to a connector with an adapter offering strain relief and cable protection as well.