

RAMPA Flathead Screws type FP
The head is chamfered to accommodate a decorative plastic cap.
Grade: 4.8

RAMPA Countersunk Screws type SB
comply with DIN 963, with slot and a 3,0 mm headbore (2,5 mm headbore at M 4).
Grade: 4.8

Sizes not included in our range can be requested.


Maryland Metrics
<http://mdmetric.com>

Type FP Article No.	Dimension	Kilos per 1000	Steel zinc plated
150 625 001	M 6 x 25	6,0	XXX
150 640 001	M 6 x 40	8,4	XXX
150 645 001	M 6 x 45	9,3	XXX
150 650 001	M 6 x 50	10,2	XXX
150 655 001	M 6 x 55	11,1	XXX
150 660 001	M 6 x 60	12,0	XXX
150 670 001	M 6 x 70	13,6	XXX

XXX = available from stock



RAMPA
Flathead Screws type FP



RAMPA
Countersunk Screws type SB

Type SB Article No.	Dimension	Kilos per 1000	Steel zinc plated
111 420 001	M 4 x 20	2,4	XXX
111 520 001	M 5 x 20	2,6	XXX
111 525 001	M 5 x 25	2,9	XXX
111 530 001	M 5 x 30	3,5	XXX
111 540 001	M 5 x 40	4,8	XXX
111 550 001	M 5 x 50	6,3	XXX
111 616 001	M 6 x 16	3,0	XXX
111 620 001	M 6 x 20	4,2	XXX
111 635 001	M 6 x 35	6,5	XXX
111 640 001	M 6 x 40	7,1	XXX
111 645 001	M 6 x 45	8,0	XXX
111 650 001	M 6 x 50	9,3	XXX
111 660 001	M 6 x 60	10,5	XXX
111 670 001	M 6 x 70	12,2	XXX
111 680 001	M 6 x 80	13,9	XXX
111 600 001	M 6 x 100	17,0	XXX
111 850 001	M 8 x 50	17,2	XXX
111 860 001	M 8 x 60	19,6	XXX
111 870 001	M 8 x 70	22,6	XXX

XXX = available from stock